

Neoflex™ 500NV Series  
REPTile


**NEOFLEX**  
FITNESS FLOORING



## The Safe Choice for Recreation.


Neoflex™ 500NV Series REPTiles are dual-durometer rubber tiles, 1m x 1m in size, available from 8 - 30 mm thick. Available in any Neoflex 500NV Series color, Neoflex™ 500NV Series REPTiles are a terrific economical choice for commercial fitness facilities with cardio areas, freestyle areas or suspension training activities.

The surface finish is made of recycled synthetic rubber with a smooth yet slip resistant finish with good grip and excellent durability. Logos, agility and functional zone markings can be in-laid in to the surface for maximum effectiveness and usability.






# Specifications.




Property	Standard	Result
Thickness		8 - 30 mm
Size		1000 mm x 1000 mm
Shore Hardness	ASTM D 2240	60°
Resilience	DIN 18032-2	49%
Tear Strength Top Layer	ASTM D 624	1.39 MPa
Tear Strength Base Layer	ASTM D 624	0.70 MPa
Taber Abrasion	ASTM C 504	0.53 gr
Remaining Indentation	DIN 53960	0.07 mm
Flammability	EN 13501-1	C <sub>fl</sub> -s1
Coefficient of Friction	ASTM D 2047-97	Dry: 1.10 Wet: 1.03

## All in one, easily installed format.

Neoflex™ 500NV Series REPTiles are supplied in 1m x 1m tiles, that are easy to install.




*without graphics*




*with graphics*


## Standard Colors.




*500NV*




*501NV*




*502NV*




*503NV*




*504NV*




*505NV*




*513NV*




*514NV*




515NV




516NV



517NV




518NV




519NV



521NV



524NV




525NV




527NV




553NV



554NV



556NV



# A Selection of Standard Colors

For real samples, contact us!